

Performance Profile Sheet (Page 1 of 2)

NCCER Training

Craft: Pipeline Corrosion Control Level 2
 Module: CT10_1-17
 Module Title: Insert and Remove Coupons



Trainee Name:

Training Program
 Sponsor:

Instructor:

Rating Levels: (1) Passed: performed task (2) Failed: did not perform task
 Also, list the date the testing for each task was completed.

Recognition: When testing for the NCCER Training Program, be sure to record Performance testing results on the Registration of Training Modules form, and submit the results to the Training Program Sponsor.

OBJECTIVE	TASK	RATING	DATE	START TIME	END TIME
2	Insert and remove corrosion coupons (CT10_1-17).				
	Identify potential abnormal operating conditions that may occur during performance of this CT, and know the appropriate actions to take in response to them.				
	Utilize the appropriate personal protective equipment according to relevant company procedures.				
	Retract coupon according to manufacturer and company procedures. Perform this function slowly, monitoring for any leaks or change in pressure.				
	Close isolation valve. Follow company procedures to isolate coupon.				
	Package and label coupon. Document the coupon's visual characteristics. Confirm that the coupon is placed in its original shipping envelope.				

Craft: Pipeline Corrosion Control Level 2
Module: CT10_1-17
Module Title: Insert and Remove Coupons



OBJECTIVE	TASK	RATING	DATE	START TIME	END TIME
	Prepare new coupon. Properly record the new coupon's information. Thoroughly clean and prepare the coupon holder and ancillary equipment for coupon installation.				
	Install the new coupon on insulating assembly. Install coupon holder according to manufacturer and company procedures. Perform this function slowly to prevent damage to the coupon and plug assembly.				
	Open the isolation valve after the coupon holder assembly is properly installed on the valve.				
	Reinsert the coupon.				
	Perform the necessary notifications upon completion of the inspection.				
	Document inspection results according to company procedure.				